



Datos útiles » Tabla de medidas de contenedores
Useful information » Table of Container Measures

Standard Container for non-perishable cargo (20')	Standard Container for non-perishable cargo (40')	High Cube Container (40')
Insulated Container	Refrigerated Container	Ventilated Container
Open Top Container (20'/40')	Platform Container (20'/40')	Flack Rack (20'/40')
Tank Container	Bulk Container	

Standard Container for non-perishable cargo (20')

	External measurements:	Length: 6,058 mm Width: 2,438 mm Height: 2,591 mm
	Internal measurements:	Length: 5,910 mm Width: 2,340 mm Height: 2,388 mm
	Entrances:	Width: 2,346 mm Height: 2,282 mm Cubic Capacity: 33.2 m3
	Weights:	Maximun weight: 24,000 Kg Tare weight: 2,080 Kg Cargo: 21,920 Kg
	Characteristics:	Corner casting for handling with cargo.


Standard Container for non-perishable cargo (40')

	External measurements:	Length: 12,192mm Width: 2,438 mm Height: 2,591 mm
	Internal measurements:	Length: 12,044 mm Width: 2,342 mm Height: 2,380 mm
	Entrances:	Width: 2,337 mm Height: 2,280 mm Cubic Capacity: 67.6 m3
	Weights:	Maximun weight: 30,480 Kg Tare weight: 3,550 Kg Cargo: 26,930 Kg
	Characteristics:	Corner casting for handling with cargo.

High Cube Container (40')

	External measurements:	Length: 12,192mm Width: 2,438 mm Height: 2,895 mm
	Internal measurements:	Length: 12,032 mm Width: 2,350 mm Height: 2,695 mm
	Entrances:	Width: 2,338 mm Height: 2,585 mm Cubic Capacity: 76.2 m3
	Weights:	Maximun weight: 30,480 Kg Tare weight: 4,150 Kg Cargo: 26,330 Kg
	Characteristics:	Corner casting for handling with cargo.

Insulated Container

	External measurements:	Length: 6,058 mm Width: 2,438 mm Height: 2,438 mm
	Internal measurements:	Length: 5,717 mm Width: 2,267 mm Height: 2,117 mm
	Entrances:	Width: 2,267 mm Height: 2,115 mm Cubic Capacity: 27.4 m3
	Weights:	Maximun weight: 24,000 Kg Tare weight: 2,800 Kg
	Characteristics:	Aluminum floor. Reinforced steel doors. Stainless steel casing. Clip-on recess.

Refrigerated Container

	External measurements:	Length: 6,058 mm Width: 2,438 mm Height: 2,591 mm
	Internal measurements:	Length: 5,498 mm Width: 2,270 mm Height: 2,267 mm
	Entrances:	Width: 2,270 mm Height: 2,210 mm Cubic Capacity: 28.3 m ³
	Weights:	Maximun weight: 25,400 Kg Tare weight: 3,040 Kg Cargo: 22,360 Kg
	Characteristics:	Aluminum floor. Reinforced teel door. Stainless steel casing Power generator recess.

Ventilated Container

	External measurements:	Length: 6,068 mm Width: 2,438 mm Height: 2,591 mm
	Internal measurements:	Length: 5,900 mm Width: 2,323 mm Height: 2,367 mm
	Ventilation:	Top: 9,000 cm ³ x side Base: 1,000 cm ³ x side Cubic Capacity: 32.6 m ³
	Weights:	Maximun weight: 24,000 Kg Tare weight: 2,650 Kg Cargo: 21,350 Kg
	Characteristics:	Sling for handling with cargo. 20,000 cm ³ permanent ventilation.


Open Top Container (20'/40')

	External measurements:	Length: 6,058 mm / 12, 192 mm Width: 2,438 mm / 2,438 mm Height: 2,591 mm / 2,591 mm
	Internal measurements:	Access from top Length: 5,792 / 11,883 mm Width: 2,225 mm / 2,152mm
	Entrances:	Lenght: 2,336 mm / 2,337 mm Height: 2,233 mm / 2,280 mm
	Weights:	Maximum: 24,000 / 30,820 kg Tare weight: 2,050 / 3,800 kg Cargo: 21,950 / 27,020 kg Central height of arches: 2,370 mm/2,380 mm Side height of arches: 2,320 mm / 2,330 mm Lenght of side panel: 2,346 mm / 2,342 mm Cubic Capacity: 32.2 m ³ / 65.6 m ³
	Characteristics:	Sling for handling with cargo (20') Hoisting up.

Platform Container (20'/40')

	External measurements:	Length: 6,058 mm / 12,192 mm Width: 2,438 mm / 2,438 mm Height: 226 mm / 628 mm
	Internal measurements:	Length of platform: 6,020 mm / 12,150 mm Width of platform: 2,413 mm / 2,290 mm Cubic Capacity: 29 m ³ / 67 m ³
	Characteristics:	Sling for handling with cargo Steel platform. Hoisting up.

Flack Rack (20'/40')

	External measurements:	Length: 6,058 mm / 12,192 mm Width: 2,438 mm / 2,438 mm Height: 2,591 mm / 2,591 mm Folded height: 555 mm / 700 mm Platform height: 271mm / 605 mm
	Internal measurements:	Cargo access / top: 5,908mm / 12,020 mm Cargo access / side: 5,508 mm / 11,730 mm Width: 2,387mm / 2,230 mm Width between struts: 2,182mm / 2,230 mm Width between shafts: 2,190 mm / 2,100 mm Height: 2,320 mm / 1,986 mm Cubic Capacity: 28.9 m ³ / 67 m ³
	Weights:	Maximum: 25,400 kg / 45,000 kg Tare weight: 2,845 kg / 5,180 kg Cargo: 22,555 kg / 39,820 kg
	Characteristics:	Fold-up spring-loaded panels Sling for handling with cargo.

Tank Container

	External measurements:	Length: 6,058 mm Width: 2,438 mm Height: 2,591 mm
---	------------------------	---

Bulk Container

	External measurements:	Length: 6,058 mm Width: 2,438 mm Height: 2,591 mm
	Internal measurements:	Length: 5,838 mm Width: 2,366 mm Height: 2,374 mm
	Front opening:	Width: 2,144 mm Height: 500 mm
	Rear opening:	Width: 280 mm Height: 300 mm Cubic capacity: 32.7 m ³
	Top openings:	500 mm diameter Maximum cargo weight: 28,030 kg Weight per container: 2,540 k
	Characteristics:	Sling of shifting with cargo and free access openings on top.